

DS201 B16 A30



Products Low Voltage Products and Systems Modular DIN Rail Products Residual Current Devices RCDs
Residual Current Circuit Breakers with Overcurrent Protection RCBO

General Information

Extended Product Type: DS201 B16 A30

Product ID: 2CSR255140R1165

EAN: 8012542655602

Catalog Description: DS201 B16 A30 - RCBO

Long Description: The DS201 series RCBO is a 1P+N in two-modules device for the protection of end user single-phase circuits against overload and short-circuit currents; protection against the effects of sinusoidal alternating and direct pulsating earth fault currents; protection against indirect contacts and additional protection against direct contacts (with sensitivity = 30 mA).

Additional Information

Country of Origin:	Italy (IT)
Customs Tariff Number:	85363030
Data Sheet, Technical Information:	2CSC400002D0209
Declaration of Conformity - CE:	9AKK106713A5588
EAN:	8012542655602
EPLAN Catalog Tree:	Electrical engineering / Protection devices / Ground fault current circuit breaker
ETIM 4:	EC000905 - Earth leakage circuit breaker
ETIM 5:	EC000905 - Earth leakage circuit breaker
ETIM 6:	EC000905 - Earth leakage circuit breaker
Environmental Information:	refer to RoHS information
Instructions and Manuals:	9AKK106354A0766
Invoice Description:	DS201 B16 A30 - RCBO
Minimum Order Quantity:	1 piece
Number of Poles:	2
Number of Protected Poles:	1
Object Classification Code:	Q
Operating Characteristic:	Instantaneous
Options Provided:	-
Package Level 1 EAN:	8012542655619
Package Level 1 Gross Weight:	1.446 kg
Package Level 1 Height:	0.088 m
Package Level 1 Length:	0.108 m
Package Level 1 Units:	5 piece
Package Level 1 Width:	0.253 m
Position of Neutral Terminals:	Right
Power Loss:	3.4 W
Product Main Type:	DS201
Product Name:	Residual Current Circuit Breaker with Overcurrent Protection
Product Net Depth:	0.069 m
Product Net Height:	0.085 m
Product Net Weight:	0.239 kg
Product Net Width:	0.035 m
Rated Current (I_n):	16 A
Rated Operational Voltage:	230-240 V AC
Rated Residual Current:	30 mA
Rated Short-Circuit Capacity (I_{cn}):	(230 / 400 V AC) 6 kA
RoHS Date:	20140127
RoHS Information:	2CSC422002K2701
RoHS Status:	Following EU Directive 2011/65/EC
Selling Unit of Measure:	piece
Standards:	IEC 61009-1 IEC 61009-2-1 EN 61009-1 EN 61009-2-1
Tripping Characteristic:	B
Type of Residual Current:	A type
Accessories Available:	Yes

