Specificații

Eaton 167594

Eaton Moeller series xPole - SPCT2 Surge Protection Device. Plug-in surge arresters, 2p, 280VAC, 2x20kA

General specifications	
PRODUCT NAME	Eaton Moeller series xPole - SPCT2 Surge protection device
CATALOG NUMBER	167594
EAN	4015081640867
PRODUCT LENGTH/DEPTH	85 mm
PRODUCT HEIGHT	67 mm
PRODUCT WIDTH	35 mm
PRODUCT WEIGHT	0.209 kg
COMPLIANCES	RoHS conform
CERTIFICATIONS	CE
MODEL CODE	SPCT2-280/2

Powering Business Worldwide

Additional information

FEATURES	Category type 2
SYSTEM CONFIGURATION TYPE	Other TN TN-S

Delivery program

APPLICATION	• Open areas • Residential buildings • Utility buildings
TYPE	Surge arrester

Technical data - electrical

CONTINUOUS VOLTAGE AT AC - MAX	280 V
DISCHARGE SURGE CURRENT (8/20) - MAX	40 kA
NOMINAL DISCHARGE SURGE CURRENT (8/20)	20 kA
NOMINAL VOLTAGE AT AC	280 V
SIGNALLING AT THE DEVICE	Optic
VOLTAGE PROTECTION LEVEL	1.4 KV

Technical data - mechanical

CONDUCTOR CROSS SECTION (FLEXIBLE, FINE-STRAND) - MAX	35 mm²
CONDUCTOR CROSS SECTION (FLEXIBLE, FINE-STRAND) - MIN	35 mm²
CONDUCTOR CROSS SECTION (SOLID, SOLID-STRAND) - MAX	25 mm²
CONDUCTOR CROSS SECTION (SOLID, SOLID-STRAND) - MIN	25 mm²
DEGREE OF PROTECTION	IP20
FRAME	2 modular spacing
MOUNTING METHOD	DIN rail (top hat rail) 35 mm
NUMBER OF CONDUCTORS WITHOUT EARTHING	2

Resurse

CATALOAGE	eaton-spct2-surge-protection-catalog-ca010005en-en-us.pdf
DESENE	eaton-xpole-spct2-surge-protection-device-dimensions.jpg
PEP ECO-PASSPORT	eaton-t2-arrestor-pep-eato-00260-v0101-en.pdf
SCHEME ELECTRICE	eaton-xpole-spct2-surge-protection-device-wiring-diagram-003.jpg

DENUMIREA PROIECTULUI:	
NUMĂRUL PROIECTULUI:	
PREGĂTIT DE:	
DATA:	

Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Irlanda
Eaton.com

© 2026 Eaton. Toate drepturile rezervate

Urmăriți-ne pe rețelele de socializare pentru a obține cele mai noi informații despre produse și asistență.