ECM48PT

Cutie distribuție



Cod ETI:	**001100400**
Grup Catalog:	**ECM Tablouri de distribuție încastrate din plastic IP40**
Tip montaj:	**Culoare aplicată**
Grad de protecție IP:	**IP40**
Dimensiune (numarul de randuri) :	**4**
Numarul de module (total / pe rand) :	**48/12**
Usa (material, culoare) :	**Plastic, Transparent**
Parte inferioara cutie (material, culoare) :	**Plastic, Alb**
Numarul de terminale PE/N (conexiuni) :	**20**
Test pentru fire:	**650 °C**
Tensiune nominală DC:	**400 V**
Curent nominal:	**63 A**
Tensiune nominală AC:	**400 V**

Pagina online a produsului

Documente

CATALOG DATE TEHNICE

MANUAL DE INSTRUCȚIUNI

DECLARAȚIE CE

FIȘIER 2D

FIȘIER 3D

ETIM

Built-in depth	**68 mm**
Width	**283 mm**
DIN-rail	✓
Type of covering	**Door**
Neutral terminal block	✓
Transparent cover/door	✓
Degree of protection (IP)	**IP40**
Mounting method	**Flush-mounted**
Signal passing door	✓
Earthing terminal block	✓
Built-in height	**656 mm**
Number of rows	**4**
Housing material	**Plastic**
Depth	**106 mm**
Built-in width	**273 mm**
Colour	**White**
Type of door	**Single**
Cover model	**Closed**
Height	**676 mm**
Width in number of modular spacings	**12**
RAL-number	**9.003**

Logistică

Produs

Greutate	**2,232 kg**
Net width	**284,5 mm**
Net height	**675,4 mm**
Net depth	**107,8 mm**
Stock unit of measure	**pcs**

Ambalare de bază

Basic packaging quantity	**1 pcs**
EAN code for a basic packaging	**3838400092977**
Basic packaging weight	**2,232 kg**
Basic Packaging Dimensions Height	**676 mm**
Basic Packaging Dimensions Width	**283 mm**
Basic Packaging Dimensions Depth	**106 mm**
Basic packaging volume	**0,02 m³**

Ambalare transport

Transport packaging quantity	**5 pcs**
EAN code for a transport packaging	**3838400092984**
Transport packaging weight	**12,28 kg**
Transport Packaging Dimensions Height	**668 mm**
Transport Packaging Dimensions Width	**577 mm**
Transport Packaging Dimensions Depth	**300 mm**
Transport packaging volume	**115,631 dm³**
Pallet quantity	**70 pcs**
Customs tariff	**85381000**

Dimension

Flush mounted distribution board

type	Dimensions							Max. allowed power losses when Max. number of devices are installed	Static load
	A	B	C	D	E	F	G	Pde	
ECM4PT/ECM4P0	232 mm	139 mm	99 mm	-	123 mm	216 mm	69 mm	>10 W	520 g
ECM8PT/ECM8P0	232 mm	211 mm	99 mm	-	201 mm	212mm	68 mm	>16 W	1040 g
ECM12PT/ECM12P0	232 mm	283 mm	106 mm	-	273 mm	212 mm	68 mm	>25 W	1560 g
ECM18PT/ECM18P0	232 mm	392 mm	106 mm	-	382 mm	212 mm	68 mm	>25 W	2340 g
ECM24PT/ECM24P0	357 mm	283 mm	106 mm	125 mm	273 mm	336 mm	68 mm	>30 W	1560 g
ECM36PT/ECM36P0	482 mm	283 mm	106 mm	125 mm	273 mm	462 mm	68 mm	>30 W	1560 g
ECM48PT/ECM48P0	676 mm	283 mm	106 mm	125 mm	273 mm	656 mm	68 mm	>30 W	1560 g
ECM2x18PT/ECM2x18P0	357 mm	392 mm	106 mm	125 mm	382 mm	336 mm	68 mm	>30 W	2340 g
ECM3x18PT/ECM3x18P0	522 mm	392 mm	106 mm	125 mm	382 mm	502 mm	68 mm	>35 W	2340 g

